

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** XBA solvent**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No relevant identified uses-mixture of substances.

Application of the substance / the mixture: Raw materials for coatings**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

Alel Ltd

Address: "General Parensov" 16

Sofia, Bulgaria

Tel.: +359 78 55 23 00

Fax. +359 78 55 22 00

e-mail: alel@dir.bg

1.4 Emergency telephone number:

European Emergency Tel.: 112

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation EC No 1272/2008 CLP:**

GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 1)

2.2 Label elements**Labelling according to Regulation EC No 1272/2008 CLP:**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:

GHS02 GHS07 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

Xylene

Hazard statements:

- H226 Flammable liquid and vapour.
H312+H332 Harmful in contact with skin or if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture: consisting of the following components.

(Contd. on page 3)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 2)

Ingredients according Regulation (EU) 830/2015:

| | | |
|--|--|---------|
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX | Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 50-100% |
| CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01- 2129485493-XXXX | n-butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336 | ≤10% |

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air and to be sure call for a doctor.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

After skin contact:

Remove contaminated clothing.

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for at least 15 minutes under running water.

Seek immediate medical advice.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters**Protective equipment:**

Wear fully protective suit.

Mouth respiratory protective device.

(Contd. on page 4)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 3)

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:**

Avoid contact with oxidising agents.

Avoid inhalation of vapors.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust, silica gel).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Keep receptacles tightly sealed.

Use in well ventilated areas.

Avoid contact with skin, eyes and clothing.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Provide ventilation for receptacles.

Information about storage in one common storage facility: Store away from oxidising agents.**Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

—GB—

(Contd. on page 5)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
|-----|--|

123-86-4 n-butyl acetate

| | |
|-----|---|
| WEL | Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
|-----|---|

Ingredients with biological limit values:

1330-20-7 Xylene

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

8.2 Exposure controls

Personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

(Contd. on page 6)

-GB-

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 5)

Eye protection:

Tightly sealed goggles



Face protection

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

| | |
|-------------------------|------------------------------------|
| Form: | Liquid |
| Colour: | According to product specification |
| Odour: | Solvent-like |
| Odour threshold: | Not determined |

| | |
|---|----------------|
| pH value: | Not determined |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | Not determined |

Flash point: 32 °C**Flammability (solid, gas):** Not applicable**Auto-ignition temperature:** Not determined**Decomposition temperature:** Not determined**Auto-ignition temperature:** Product is not selfigniting.**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 0.8 Vol % |
| Upper: | 7.5 Vol % |

Vapour pressure: Not determined**Density:** Not determined

(Contd. on page 7)

Safety data sheet
 complying with Regulation 1907/2006/EC (REACH Regulation), EU
 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 6)

Relative density Not determined
Vapour density Not determined
Evaporation rate Not determined

Solubility in / Miscibility with water: Not miscible

Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic: Not determined

Kinematic: Not determined

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid Oxidising agents

10.5 Incompatible materials Oxidising agents

10.6 Hazardous decomposition products

Carbon monoxide

Carbon dioxide

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity**

Harmful in contact with skin or if inhaled.

LD/LC50 values relevant for classification:**1330-20-7 Xylene**

| | | |
|------------|---------|----------------------|
| Dermal | LD50 | >1700 mg/kg (rabbit) |
| Inhalative | LC50-4h | 5000 ppm (rat) |

123-86-4 n-butyl acetate

| | | |
|------------|---------|----------------------|
| Oral | LD50 | 10768 mg/kg (rat) |
| Dermal | LD50 | 17600 mg/kg (rabbit) |
| Inhalative | LC50-4h | 390 ppm (rat) |

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 7)

Carcinogenicity Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information**12.1 Toxicity****Aquatic toxicity:** No further relevant information available.**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information**14.1 UN-Number****ADR, IMDG, IATA**

UN1307

14.2 UN proper shipping name**ADR**

1307 XYLENES

IMDG, IATA

XYLENES

(Contd. on page 9)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 8)

14.3 Transport hazard class(es)**ADR, IMDG, IATA**

| | |
|--|-----------------------------|
| Class | 3 Flammable liquids. |
| Label | 3 |
| 14.4 Packing group | |
| ADR, IMDG, IATA | III |
| 14.5 Environmental hazards: | Not applicable. |
| 14.6 Special precautions for user | Warning: Flammable liquids. |
| Danger code (Kemler): | 30 |
| EMS Number: | F-E,S-D |
| 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |

Transport/Additional information:**ADR**

| | |
|--------------------------------|-------------------------|
| Limited quantities (LQ) | 5L |
| Transport category | 3 |
| Tunnel restriction code | D/E |
| UN "Model Regulation": | UN1307, XYLENES, 3, III |

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3**National regulations:****Other regulations, limitations and prohibitive regulations****Substances of very high concern (SVHC) according to REACH, Article 57**

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment:

Has been performed for the main ingredients of the product.

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation), EU
2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 10.01.2018

Version number 2

Revision: 16.03.2015

Trade name: XBA solvent

(Contd. of page 9)

Relevant phrases

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.

Department issuing SDS:

SUSTCHEM Engineering Ltd
REACH & Chemical Services Department
144, 3rd Septemvriou, GR 112 51, Athens, Greece
Tel.: +30 210 8252510 Fax: +30 210 8252575
E-mail: info@suschem.gr
Website: www.sustchem.gr

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

*** Data compared to the previous version altered.**